



DESCRIPTION - WALL MOUNT ENCLOSURES

Optima's W Series of wall mount enclosures designed for applications where space is tight but storage needs are critical. W Series 19" rack mount cabinets handle your back room requirements and help you organize critical system and network components such as hubs, concentrators, routers, A/V and security equipment. Count on Optima to offer industry leading standards and full array of accessories for optimum efficiency.

FEATURES

- 3 Heights: 12U (23 1/8"), 20U (37 1/8"), 26U (48 1/8")
- 2 Depths: 14", 20"
- 14 gauge steel construction.
- 3" diameter cable access ports (top/bottom).
- Adjustable, 19" mounting rails, 2 x EIA-310 (10-32 std).
- Vented or solid sides.
- Universal hinging permits mounting for left or right opening.
- Plexiglas or solid doors with dual hinges for front & rear access.
- Key locks front & rear.

ORDERING INFORMATION



1,2 SIDE PANEL

WM > Solid
WV > Vented
ZZ > Custom

3,4 HEIGHT

21 > 12U (21.12"/536mm)
35 > 20U (35.12"/892mm)
45 > 26U
ZZ > Custom

5,6 WIDTH

19 > 19" (17.81"/452.4mm)
ZZ > Custom

7,8 RAIL DEPTH

14 > 14" (355.6 mm)
20 > 20" (508 mm)
ZZ > Custom

9,10 DOOR

WD > Solid
WP > Plexiglass
ZZ > Custom

11 BODY COLOR

1 > Black (207)
2 > Sky Blue (210)
3 > White (931)
4 > Deep Charcoal (209)
5 > Light Gray (201)
6 > Beige (205)
Z > Custom

SPECIFICATIONS

CABINET SIZE	PANEL HEIGHT	OVERALL DIMENSIONS			MAX. RAIL DEPTH	WEIGHT
		HEIGHT (IN.)	WIDTH (IN.)	DEPTH (IN.)		
xx-211914-xx	12U (21.0")	23 1/8	21 1/4	20 3/16	14"	75 lbs
xx-211920-xx	12U (21.0")	23 1/8	21 1/4	26 3/16	20"	90 lbs
xx-351914-xx	20U (35.0")	37 1/8	21 1/4	20 3/16	14"	95 lbs
xx-351920-xx	20U (35.0")	37 1/8	21 1/4	26 3/16	20"	110 lbs
xx-451914-xx	26U (45.5")	48 1/8	21 1/4	20 3/16	14"	110 lbs
xx-451920-xx	26U (45.5")	48 1/8	21 1/4	26 3/16	20"	130 lbs

ACCESSORIES	PART #	DESCRIPTION	PART #	DESCRIPTION	
CANTILEVERED SHELVES	CS-1912-S	Solid 12 1/2" Depth	15-AMP POWER STRIP	WPO-0691RM	Rack Mount 125V 15A 6/Single Outlet Config.
	CS-1912-V	Vented 12 1/2" Depth		WPO-1091RM	Rack Mount 125V 15A 10/Single Outlet Config.
	CS-1914-S	Solid 14 1/2" Depth			
	CS-1914-V	Vented 14 1/2" Depth			
CABLE MANAGEMENT RING PANELS	CMR-1901	1U (1.75")	EXHAUST FAN	WCF-250	250 CFM, 35 watt 115 VAC, 80" cord
	CMR-1902	2U (3.50")			
MOUNTING RAIL SETS	WMR-21	12U Panel Height	BUS BAR	WWBB-19	Copper 1/4"x19" long
	WMR-35	20U Panel Height			
	WMR-45	26U Panel Height			
FILLER PANELS	WMP-0119	1U Panel Height			
	WMP-0319	2U Panel Height			
	WMP-0519	3U Panel Height			